



Large Scale Minis

Host Club:	
Event:	

Competitor Name:	
Scrutineer	

Scrutineering Record

For Inspection	Pre Event	Qual 1	Qual 2	Qual 3	Qual 4	Qual 5	Qual 6	1/4 Final	1/5 Final	Final	Comments	Explanatory notes for scrutineer
Scrutineers initials												compulsory
2 Servos Only												Steering servo and brake/throttle servo
Springs: Yellow; Red; Violet; or Blue												As outlined in specification
Weight Min 10.0Kg no fuel												Complete with body battery and tyres
Brakes Cable Front, Layshaft Rear												connected and functional when operating servo lever
Brakes working (must check with radio)												operate brakes using radio while rolling vehicle. At full brake achieve vertical wheel tyre lock when pushing vehicle
Foam bumper 15mm clearance												Foam can be shaped in any way providing that at any given point from the plastic support it extends past a minimum of 15mm
Remote Activated Kill Switch (if fitted must demonstrate working)												optional- if fitted must show to vbe functioning. Start mini and switch off via radio
E on body above kill switch												The position of the ignition cut---out switch must be marked on the body shell with a white circular decal, 30mm in diameter, outlined in red with a red E in the centre.
Body and window cut out												compulsory to cut out the 2 front side door windows. either rear windscreen can also be cut out or alternatively both side rear windows (NOT BOTH) The body shell must be painted or wrapped with all windows to remain clear.
Body condition												In good condition so that Marshals and scrutineering can easily handle the vehicle. No sharp or extruding screw
Return spring on Carbi working												check by operating linkage connected to carbi
OEM Battery Mount												confrm anchored at both ends and battery is secularly fastened
OEM Sway Bars												Connected and not modified
OEM Gearing (incl Diffs)												48th plastic pinnion and check roll out by marking one front and one rear tyre and making sure both revolve equally
Control Tyres GRP S5												GRP S5 (Mark 2 car sets) allocated number
OEM Exhaust No Mods												visual inspection for any modification. A lso inspect for cracked pipe/manifold or damage to pipe causing exessive noise
Clutch Engage RPM												Clutch not to engage beyond 9500rpm (+5% tolerance allowed/9975rpm)
Engine check												Check engine does not exceed 26cc
Tyre marking												All tyres (a maximum of 2 full sets) must be marked prior to the event starting
Walbro Carburators												check stamping in carbi body- must be WT603, WT668 & WT997
Side body intrusion guards												Side intrusion bars (if fitted) must be made of nylon, plastic, carbon fibre or aluminium angle (Bunnings I/N:1067823) 20x12x1.4mm thick only. Corners must be rounded and sharp edges removed
Rear wing												IOEM only and only original mounting orientation

Comments: