



Large Scale Minis

	Host Club:	
	Event:	

Competitor Name:	
Scrutineer	

Scrutineering Record

For Inspection	Pre Event	Qual 1	Qual 2	Qual 3	Qual 4	Qual 5	Qual 6	1/4 Final	1/5 Final	Final	Comments	Explanatory notes for scrutineer
Scrutineers initials												compulsory
2 Servos Only												Steering servo and brake/throttle servo
Springs: Yellow; Red; Violet; or Blue												As outlined in specification
Weight Min 10.0Kg no fuel												Complete with body battery and tyres
Brakes Cable Front, Layshaft Rear												connected and functional when operating servo lever
Brakes working (must check with radio)												operate brakes using radio while rolling vehicle. At full brake achieve vertical wheel tyre lock when pushing vehicle
Foam bumper 15mm clearance												Foam can be shaped in any way providing that at any given point from the plastic support it extends past a minimum of 15mm
Remote Activated Kill Switch (if fitted must demonstrate working)												optional- if fitted must show to vbe functioning. Start mini and switch off via radio
E on body above kill switch												The position of the ignition cut---out switch must be marked on the body shell with a white circular decal, 30mm in diameter, outlined in red with a red E in the centre.
Body and window cut out												compulsory to cut out the 2 front side door windows. either rear windscreen can also be cut out or alternatively both side rear windows (NOT BOTH) The body shell must be painted or wrapped with all windows to remain clear.
Body condition												In good condition so that Marshals and scrutineering can easily handle the vehicle. No sharp or extruding screw
Return spring on Carbie working												check by operating linkage connected to carbi
OEM Battery Mount												confirm anchored at both ends and battery is securely fastened
OEM Sway Bars												Connected and not modified
OEM Gearing (incl Diffs)												48th plastic pinnion and check roll out by marking one front and one rear tyre and making sure both revolve equally
Control Tyres GRP S5												GRP S5 (Mark 2 car sets) allocated number
OEM Exhaust No Mods												visual inspection for any modification. Also inspect for cracked pipe/manifold or damage to pipe causing excessive noise
Clutch Engage RPM												Clutch not to engage beyond 9500rpm (+5% tolerance allowed/9975rpm)
Engine check and marking												Engine number mark with tyre pen same as tyre number after checking is approved motor not exceeding 26cc
Walbro Carburetors												check stamping in carbi body- must be WT603, WT668 & WT997
Side body intrusion guards												Non-OEM side body intrusion guards – Approved Materials: plastic, nylon or carbon fibre
Rear wing												IOEM only and only original mounting orientation

Comments: